




JF-800/720/700/20/930 标准公制轴承
Metric Standard Bushing



内外倒角

S_3	C_o	C_i	β
0.75	0.5 ± 0.3	0.25 ± 0.2	$35^\circ \pm 5^\circ$
1.00	0.6 ± 0.3	0.30 ± 0.2	$35^\circ \pm 5^\circ$
1.50	0.7 ± 0.3	0.50 ± 0.3	$35^\circ \pm 5^\circ$

S_3	C_o	C_i	β
2.00	1.2 ± 0.4	0.50 ± 0.3	$30^\circ \pm 5^\circ$
2.50	1.8 ± 0.6	0.60 ± 0.3	$45^\circ \pm 5^\circ$

※标准直套标注方式：Standard Bushing Label Mode JF-800□ 1010

单位unit:mm

型号规格 Designation	D _i	D _o	轴径(h8) D _s	座(H7) D _H	压装后 内孔公差 D _{i,a}	配合间隙 C _D	壁厚 S ₃	油孔 d _L	B ⁰ _{-0.40}						
									10	15	20	25	30	40	50
JF-800 □	10	12	10 _{-0.022}	12 ^{+0.018}	+ 0.148 + 0.010	0.170 0.010	0.995 0.935	4	1010	1015	1020				
JF-800 □	12	14	12 _{-0.027}	14 ^{+0.018}		0.175 0.010			1210	1215	1220				
JF-800 □	14	16	14 _{-0.027}	16 ^{+0.018}					1410	1415	1420				
JF-800 □	15	17	15 _{-0.027}	17 ^{+0.018}					1510	1515	1520				
JF-800 □	16	18	16 _{-0.027}	18 ^{+0.018}					1610	1615	1620				
JF-800 □	18	20	18 _{-0.027}	20 ^{+0.021}	+ 0.151 + 0.010		0.178 0.010	1.490 1.430	6	1810	1815	1820	1825		
JF-800 □	20	23	20 _{-0.033}	23 ^{+0.021}	+ 0.161 + 0.020	0.194 0.020	2010			2015	2020	2025			
JF-800 □	22	25	22 _{-0.033}	25 ^{+0.021}			2210			2215	2220	2225			
JF-800 □	24	27	24 _{-0.033}	27 ^{+0.021}			2410			2415	2420	2425	2430		
JF-800 □	25	28	25 _{-0.033}	28 ^{+0.021}						2515	2520	2525	2530		
JF-800 □	26	30	26 _{-0.033}	30 ^{+0.021}			+ 0.181 + 0.040	0.214 0.040	1.980 1.920	8		2615	2620	2625	2630
JF-800 □	28	32	28 _{-0.033}	32 ^{+0.025}	+0.185 +0.040	0.218 0.040		2815			2820	2825	2830	2840	
JF-800 □	30	34	30 _{-0.033}	34 ^{+0.025}				3015			3020	3025	3030	3040	
JF-800 □	32	36	32 _{-0.039}	36 ^{+0.025}				3215			3220	3225	3230	3240	
JF-800 □	35	39	35 _{-0.039}	39 ^{+0.025}							3520	3525	3530	3540	3550
JF-800 □	38	42	38 _{-0.039}	42 ^{+0.025}									3820	3825	3830
JF-800 □	40	44	40 _{-0.039}	44 ^{+0.025}								4020	4025	4030	4040

JF-800/720/700/20/930 标准公制轴承 Metric Standard Bushing

单位unit:mm

型号规格 Designation	D _i	D _o	轴径(h8) D _s	座(H7) D _H	压装后 内孔公差 D _{l,a}	配合间隙 C _D	壁厚 S ₃	油孔 d _L	⁰ _{-0.40} B								
									25	30	40	50	60	80	90	100	
JF-800 □	45	50	45 -0.039	50 ^{+0.025}	^{+0.225} ^{+0.080}	0.264 0.080	2.460 2.400	8	4525	4530	4540	4550					
JF-800 □	50	55	50 -0.039	55 ^{+0.030}		0.269 0.080				5030	5040	5050	5060				
JF-800 □	55	60	55 -0.046	60 ^{+0.030}		^{+0.230} ^{+0.080}			0.276 0.080		5530	5540	5550	5560			
JF-800 □	60	65	60 -0.046	65 ^{+0.030}							6030	6040	6050	6060			
JF-800 □	65	70	65 -0.046	70 ^{+0.030}							6530	6540	6550	6560			
JF-800 □	70	75	70 -0.046	75 ^{+0.030}							7030	7040	7050	7060	7080		
JF-800 □	75	80	75 -0.046	80 ^{+0.030}	^{+0.235} ^{+0.080}	0.281 0.080		9.5		7530	7540	7550	7560				
JF-800 □	80	85	80 -0.046	85 ^{+0.035}					0.289 0.080			8040	8050	8060	8080		
JF-800 □	85	90	85 -0.054	90 ^{+0.035}							8530		8550	8560	8580		85100
JF-800 □	90	95	90 -0.054	95 ^{+0.035}								9050	9060	9080		90100	
JF-800 □	95	100	95 -0.054	100 ^{+0.035}									9560	9580	9590	95100	
JF-800 □	100	105	100 -0.054	105 ^{+0.035}									10060	10080	10090	100100	
JF-800 □	105	110	105 -0.054	110 ^{+0.035}									10560	10580		105100	
JF-800 □	110	115	110 -0.054	115 ^{+0.035}									11060	11080		110100	
JF-800 □	115	120	115 -0.054	120 ^{+0.035}								11550		11580			
JF-800 □	120	125	120 -0.054	125 ^{+0.040}	^{+0.240} ^{+0.080}	0.303 0.080						12050	12030			120100	
JF-800 □	125	130	125 -0.063	130 ^{+0.040}												125100	
JF-800 □	130	135	130 -0.063	135 ^{+0.040}									13060			130100	
JF-800 □	135	140	135 -0.063	140 ^{+0.040}									13560	13580			
JF-800 □	140	145	140 -0.063	145 ^{+0.040}									14060	14080		140100	
JF-800 □	150	155	150 -0.063	155 ^{+0.040}									15060	15080		150100	